
Cylinder Information

Safety Features

Your Safefill cylinder is protected in three ways.

- An Overfill Protection Device designed to leave space (about 20%) in the cylinder, allowing gas expansion (see SAFE USE).
- A Back Check Valve that prevents accidental release of gas if the valve is accidentally opened, e.g. if no regulator is attached.
- A Pressure Relief Valve that in the event of external circumstances (e.g.excessive heat) causing a pressure build up, will release gas to the atmosphere so that a safe-pressure is restored.



- 1 Max fill level
- 2 Pressure relief valve
- 3 Safefill lock-off valve
- 4 Fill connector
- **5** Overfill protection device

Maintenance

If used properly (in accordance with these instructions) your Safefill cylinder requires no maintenance. If cleaning is required, the cylinder can be wiped using diluted detergent and a clean cloth.

Safe Use (see diagram) This cylinder is intended for leisure use only. Use only in accordance with these instructions.

- •DO fill and use the cylinder with the cylinder in an **UPRIGHT** position.
- •DO NOT tamper with the fill connector (4) or pressure relief valve (2) or use if the fill connector (4) is damaged.
- •DO NOT exceed max fill levels from empty:

5.0Kg (~ 40cm high) cylinder- 8.5L 7.5Kg (~48cm high) Cylinder- 14.5L 10Kg (~ 58cm high) cylinder- 19.5L

- •DO NOT fill or use the cylinder if you suspect any part is faulty or damaged or the cylinder has overfilled.
- •ONLY transport with the valve tap in a closed position even when connected for use.

EC Declaration of Conformity

In accordance with OI: L218/82/2008 (768/2008/EC)

Product identification: Safefill User Refillable LPG Cylinders for leisure use only.

Manufacturer: HPC Research S.r.o. U Stadionu 615 CZ330 12 Horni Briza (ID-No.: 29132908)

This declaration of conformity is issued under the sole responsibility of Green Boxline Ltd. Great Fenton Business Park, Fenton, Stoke-on-Trent, ST4 4LZ, United Kingdom

Range of the declaration: HPC Research/Safefill cylinders of sizes 5Kg to 14 Kg. The product described above is in conformity with the relevant Community harmonisation legislation: 2014/68/EU The Pressure Equipment Directive.

References to the relevant harmonised standards used or references to the specifications in relation to which conformity is declared:

- -SI 2016/1105 The Pressure Equipment (Safety) Regulations 2016,
- -BS EN 13953 2015 Pressure Relief Valve.
- -ISO 11119-3 2013 Composite Gas Cylinders **Specification and Test**

Notified Body: TUV SUD Czech s.r.o. No. 1017

Signed by:

Name: N. Worthington **Position:** Director

For and on behalf of Green Boxline Ltd at Fenton, UK

On: 5th March 2019 DJF/AST 5/3/2019

Contact us

Safefill, Great Fenton Business Park, Grove Road, Fenton, Stoke-on-Trent, ST4 4LZ

01782 414526 | info@safefill.co.uk | www.safefill.co.uk



Congratulations on buying a Safefill refillable gas cylinder, manufactured to the highest quality and safety standards.

Please register your cylinder online at www.safefill.co.uk

Safefill cylinders are lighter than steel cylinders and, because the cylinders are translucent, it is possible to check the amount of liquefied gas inside.



All gas appliances have the potential to be hazardous if not used properly. The key to safety is common sense, so please read and follow the safety advice contained in this leaflet and ensure you pay attention when filling or connecting your cylinder as you will then be confident that all the safety features are operating correctly.



Operation & Use

IMPORTANT: FIRST FILLING ONLY

When filling the cylinder for the FIRST TIME it is important to limit the fill to the following amounts:

5kg cylinder- fill to 6L max. 7.5kg cylinder- fill to 10L max. 10kg cylinder- fill to 15L max.

If you experience any difficulties seek advice from your retailer or refill centre.

Max fill levels from empty: 5.0Kg (~ 40cm high) cylinder- 8.5L 7.5Kg (~48cm high) Cylinder- 14.5L 10Kg (~ 58cm high) cylinder- 19.5L

Cylinders should always be transported with the valve tap in a closed position even when connected for use.

Filling the cylinder

Individual LPG providers give instructions at the pump on how to use their dispenser. The cylinder MUST be filled in an upright position. During filling check the level of fill. See "How to fill your Safefill cylinder" in this leaflet and labelled on the Safefill cylinder. If in any doubt seek advice from your retailer or refill centre.

Connecting your appliance

Make sure the Safefill lock-off valve (3) is closed when fitting your regulator/ pigtail. We recommend you use the latest Hand wheel tightening type propane pigtail / propane regulator when connecting to the Safefill cylinder. (Note the thread is left handed so you tighten in an anticlockwise direction)

Recycling

All parts of your Safefill cylinder are recyclable. Return the cylinder to your nearest retailer or see the Safefill website for further details.



Filling Instruction Tab



Warranty

Should you experience defects due to material or manufacturing faults during private use of the cylinder within 10 years of purchase, we shall be liable for warranty in accordance with statutory provisions provided that:

- The cylinder was not put to any use other than that intended
- Was not tampered with
- Was not used with the wrong accessories, e.g. incorrect regulator
- Was not worked on by a non-Safefill approved workshop

The warranty is valid in connection with the receipt and begins on the day of purchase as given in the receipt. If during the warrantee period the cylinder becomes defective contact the retailer from whom you purchased it.

Legal Notice

In the event of dispute the law of England and Wales shall take precedence. This warranty does not reduce your statutory rights in any way.

In the interest of providing better information regarding product quality & or safety Safefill may alter or amend the information provided in information sheets such as this.

Green Boxline Limited, Safefill, Great Fenton Business Park, Fenton, Stoke-on-Trent, ST4 4LZ, England

riease eriter tri	le dealer Harrie arid address.

Dlasco optor the dealer name and address.